

All Set with a Tap for Success

Your Wireless Business Presentation Made Simple and Quick




BenQ Business Projectors tapNshow™

Your tapNshow™ Companion for Wireless Business Presentation

Transform your professional presentations into great business results in a simple tap with tapNshow™! BenQ's NFC wireless solution brings to you the ultimate wireless presentation experience. Using an NFC smart device and a simple, quick swipe, you can project your confidence and impress your audience in an instant!



Because it matters



I Model Name

I MW665+

I MX666+

I MW526

I MX570

Basic Information					
Projection System	DLP	DLP	DLP	DLP	DLP
Native Resolution	WXGA(1280x800)	XGA (1024x768)	WXGA(1280x800)	XGA (1024x768)	XGA (1024x768)
Brightness	3200 ANSI lumens	3500 ANSI lumens	3500 ANSI lumens	3200 ANSI lumens	3200 ANSI lumens
Contrast Ratio	13000:1	13000:1	13000:1	13000:1	13000:1
Display Color	30 Bits (1.07 billion colors)	30 Bits (1.07 billion colors)	30 Bits (1.07 billion colors)	30 Bits (1.07 billion colors)	30 Bits (1.07 billion colors)
Lens	F=2.59~2.87, f=16.88~21.88	F=2.59~2.87, f=16.88~21.88	F=2.56~2.8, f=21~23.1	F=2.59~2.87, f=16.88~21.88	F=2.59~2.87, f=16.88~21.88
Aspect Ratio	Native 16:10 (5 aspect ratio selectable)	Native 4:3 (5 aspect ratio selectable)	Native 16:10 (5 aspect ratio selectable)	Native 4:3 (5 aspect ratio selectable)	Native 4:3 (5 aspect ratio selectable)
Throw Ratio	1.21~1.57	1.51~1.97	1.5~1.65	1.51~1.97	1.51~1.97
Clear Image Size (Diagonal)	44" ~ 230"	38" ~ 195"	53"~146"	60"~140"	60"~140"
Maximum Image Size (Diagonal)	300"	300"	300"	300"	300"
Zoom Ratio	1.3:1	1.3:1	1.1:1	1.3:1	1.3:1
Lamp Wattage	210W	240W	196W	190W	190W
Lamp Life Hours(Normal/Economic/SmartEco/LampSave/LumenCare)	4500/5000/6500/10000/2100 constant brightness	3500/5000/6500/NA/NA	4500/6000/6500/10000/NA	4500/6000/6500/10000/NA	4500/6000/6500/10000/NA
Keystone Adjustment	2D,Vertical +/- 30 degrees, H +/- 25 degrees	2D,Vertical +/- 30 degrees, H +/- 25 degrees	1D,Vertical +/- 40 degrees	1D,Vertical +/- 40 degrees	1D,Vertical +/- 40 degrees
Projection Offset	120%±5%	125%±5%	100%±5%	115%±5%	115%±5%
Resolution Support	VGA(640 x 480) to WUXGA_RB*(1920X1200)	VGA(640 x 480) to WUXGA_RB*(1920X1200)	VGA(640 x 480) to WUXGA_RB*(1920X1200)	VGA(640 x 480) to WUXGA_RB*(1920X1200)	VGA(640 x 480) to WUXGA_RB*(1920X1200)
HDTV Compatibility	480i, 480p, 576i, 576p, 720p, 1080i, 1080p	480i, 480p, 576i, 576p, 720p, 1080i, 1080p	480i, 480p, 576i, 567p, 720p, 1080i, 1080p	480i, 480p, 576i, 567p, 720p, 1080i, 1080p	480i, 480p, 576i, 567p, 720p, 1080i, 1080p
Video Compatibility	NTSC, PAL, SECAM	NTSC, PAL, SECAM	NTSC, PAL, SECAM	NTSC, PAL, SECAM	NTSC, PAL, SECAM
Interface					
Computer in (D-sub 15pin)	x 2 (shared with component video)	x 2 (shared with component video)	x 2 (shared with component video)	x 2 (shared with component video)	x 2 (shared with component video)
Monitor out (D-sub 15pin)	x 1	x 1	x 1	x 1	x 1
HDMI (v1.4a)	x 1	x 1 share with MHL(1.2)	x 1	x 1	x 1
Composite Video in (RCA)	x 1	x 1	x 1	x 1	x 1
S-Video in (Mini DIN 4pin)	x 1	x 1	x 1	x 1	x 1
Audio in (Mini Jack)	x 1	x 1	x 1	x 1	x 1
Audio L/R in (RCA)	x 1	x 1	No	No	No
Audio out (Mini Jack)	x 1	x 1	x 1	x 1	x 1
Microphone in (Mini Jack)	No	No	No	No	No
Speaker	2W x 1	10W x 1	2W x 1	10W x 1	10W x 1
LAN (RJ45)	x 1 (LAN Control & LAN Display & Audio)	x 1 (LAN Control & LAN Display & Audio)	No	x 1 (LAN Control)	x 1 (LAN Control)
USB (Type A)	x 1 (USB Reader & Wireless Display & Remote Desktop)	x 1 (USB Reader & Wireless Display & Remote Desktop)	No	No	No
USB (Type B)	No	No	No	No	No
USB (Type Mini B)	x 1 (USB Display & Download)	x 1 (USB Display & Download)	x 1 (Download & Page up/down)	x 1 (Download & Page up/down)	x 1 (Download & Page up/down)
DC 12V Trigger (3.5mm Jack)	No	No	No	No	No
RS232 (DB-9pin)	x1	x1	x1	x1	x1
Dimensions (WxHxD)	312 x 104 x 244 mm	312 x 104 x 244 mm	283 x 222 x 95 mm	283 x 222 x 95 mm	283 x 222 x 95 mm
Weight	2.8kg (6.17 lbs)	2.75kg (6.06 lbs)	1.95kg(4.3 lbs)	1.95kg(4.3 lbs)	1.95kg(4.3 lbs)
Power Supply	AC 100 to 240 V, 50/60 Hz	AC 100 to 240 V, 50/60 Hz	AC 100 to 240 V, 50/60 Hz	AC 100 to 240 V, 50/60 Hz	AC 100 to 240 V, 50/60 Hz
Typical Power Consumption	303W	375W	270W	280W	280W
Stand-by Power Consumption	<0.5W (Network standby <6W)	<0.5W (Network standby <6W)	< 0.5W	< 0.5W(Network standby <6W)	< 0.5W(Network standby <6W)
Acoustic Noise (Typ/Eco.)	33/28 dBA	33/30 dBA	33/28 dBA	33/28 dBA	33/28 dBA
Operating Temperature	0~40°C	0~40°C	0~40°C	0~40°C	0~40°C
Accessories (Standard)					
Carry Bag	x 1	x 1	No	No	No
Remote Control w/ Battery	x 1	x 1	x 1	x 1	x 1
Power Cord (by region)	x 1	x 1	x 1 (1.8m)	x 1	x 1
User Manual CD	x 1 (24L)	x 1 (24L)	x 1 (24L)	x 1 (24L)	x 1 (24L)
Quick Start Guide	x 1 (18L)	x 1 (18L)	x 1 (18L)	x 1 (18L)	x 1 (18L)
Warranty Card (by region)	x 1	x 1	x 1	x 1	x 1
VGA(D-sub 15pin) Cable	x 1	x 1	x 1	x 1	x 1
Lens cover	x 1	x 1	No	No	No
Accessories (Optional)					
Carry Bag	Yes	Yes	Yes	Yes	Yes
Spare Lamp Kit	Yes	Yes	No	Yes	Yes
3D Glasses	Yes	Yes	No	Yes	Yes
Unique Accessory	No	No	No	No	No
Compatibility					
Quick Wireless NFC Kit	Yes	Yes	No	No	No
VGA Wireless Dongle-QPro	Yes	Yes	Yes	Yes	Yes
Quick USB	Yes	Yes	No	No	No
Qpresenter Pro	Yes	Yes	No	No	No