

MasterWatt Lite 230V 700W

Lighten the Load



Power on. We want the MasterWatt Lite Series to be that simple. In the box are all the essentials of a reliable engine so you don't have to think about it. We added higher-end perks like Active PFC and PWM technology for more stability, and made sure we met ErP 2013 and CE ratings for safety and low energy impact. It's the survival kit for reliable, affordable power.

Features

Advanced Circuit Design – Active PFC + PWM combined with dual forward topology and double EMI filter enhances power output efficiency and increases the performance and stability of your system

Silent and Durable Fan – Cooler Master's 120mm HDB temperature control fan can operate more smoothly without friction, which makes it quiet and more durable.

Green Power – Compliant with ErP 2013 Lot6, which guarantees that your PSU will use less than 1W on system standby and lower than 45% transferring efficiency on 5V standby.

Safety Guardian – Full protection (OCP/OVP/UVP/SCP/OPP) with built-in Over Temperature Protection (OTP). Minimizes the risk of damage from power outages.

80 Plus Standard 230V EU Certified – 85% efficiency typically.

Specifications & Packing Information

	MPX-7001-ACABW				
	MasterWatt Lite 230V 700W				
Туре		Intel Form Factor ATX 12V V2.31			
Dimensions (LxWxH)		150 x 140 x 86mm			
Input Voltage		200-240 Vac			
Input Current		3.5 – 5A			
Input Frequency Range		47 - 63Hz			
PFC		Active PFC (>0.9 typical)			
Power Good Signal					
Hold Up Time		>10ms at 100% full load@230Vac			
Efficiency		85% @ Typical Load			
	>100,000 Hours				
2007 1	120mm HDB fan				
100% Load					
	TUV, CE, BSMI, FCC, cTUV-Rhus, KC, CCC, EAC, RCMC				
	OVP/UVP/OPP/OTP/OCP/SCP				
Certification		80 PLUS Standard 230V EU			
ErP 2013 Complaint		Yes			
20+4 Pin MB	x 1				
	x 1				
Гюрру					
Warranty					
EU / PH / AU	4719512055625				
UK	4719512055762				
EU / PH / AU	884102030697				
UK	884102030833				
Net weight		1.378 Kg			
Gross weight		1.765 Kg			
Carton dimension (L x W x H)		L: 22.70Cm x W: 23.80Cm x H: 12.00Cm			
Unit / Carton	Carton/ Pallet	Pcs / Pallet			
6	24	144			
20' w/pal	40' w/pal	40' HQ w/pal			
	Range al 20% Load 50% Load 50% Load 100% Load 100% Load int 20+4 Pin MB 4+4 Pin CPU 6+2 Pin PCI-e SATA Peripheral Floppy EU / PH / AU UK EU / PH / AU UK LU / PH / AU UK I (L x W x H) Unit / Carton	$\begin{tabular}{ c $			



Features







Certified 85% efficiency typically.

Silent and Durable 120mm HDB Fan

Active PFC + PWM combined with dual forward topology



Output Rating

AC Input	200-240V~ 3.5A 50-60Hz					
DC OUTPUT	+3.3V	+5V	+12V	-12V	+5Vsb	
	22A	22A	54A	0.3A	2.5A	
OUTPUT POWER	13	0W	648W	3.6W	12.5W	
			700W			

Cable info

