

PV3200U | 32" 4K BenQ Video Editing Monitor

Edit Sharp. Hear Clear.

BenQ PV3200U is a 32-inch 4K monitor designed for video creators who demand both visual and audio precision. With 95% P3, 100% Rec.709 coverage, and built-in 2.1-channel speakers, it delivers color and sound exactly as you want your audience to experience them. ICCsync, M-book Mode, and the Hotkey Puck simplify workflows and support both Mac and Windows environments.



No Surprise from Edit to Upload

PV3200U covers 100% Rec.709 and 95% P3 for consistent color from edit to upload. Instantly switch modes with the Wireless Hotkey Puck to preview your content and prevent unexpected color shifts on YouTube, Vimeo, and other video platforms.



Crisp Voices. Clear Mix. No Extra Gear.

Studio Mode and built-in 2.1ch speakers deliver unprocessed, true-to-source sound with clear vocals and balanced bass, providing a reliable reference when you need a break from headphones during long editing sessions.



Colors You Can Trust

BenQ AQCOLOR ensures accurate reproduction, delivering out-of-the-box color precision with Delta E \leq 2, corner-to-corner uniformity, and a factory calibration report. Every feature is rigorously tested for consistency, giving creators total color confidence.



All-in-One USB-C Connection

Quickly transfer data and deliver power up to 65W. Your Thunderbolt 3/4 devices are compatible with USB-C on BenQ displays, ensuring consistent and seamless work efficiency.



Screen Size	Model Name	PV3200U
Aspect Ratio 16.9 16.9 16.9 16.9 16.9 16.9 16.9 16.9 16.9 14.0 14.0 14.0 14.0 14.0 14.0 14.0 14.0 16.0		
Panel Type Panel Type Pacesolution (max.) 33840/2160 PP		
Resolution (max.) 3440x2160 PPP 140 140 Previnty Angle (L/R) (CR>-10) 187/178* 180 Previnty Angle (L/R) (CR>-10) 180 Previnty Angle (L/R) (CR) (CR>-10) 180 Previnty Angle (L/R) (CR) (CR) (CR) (CR) (CR) (CR) (CR) (C		
Pri	**	
Viewing Angle (UR) (CR>10) 1787/78' Brightness (typ.) 350 HOR HOR 100's aRGB; 100's Rec.709; 95's P3 Color Gamut 100's aRGB; 100's Rec.709; 95's P3 Factory Calibration Report Yes Delta (Eyrg) 92 Calman verified Yes Native Contrast 1000:1 Refresh Rate (H2) 60 Usplay Area 957.3 x 392.2 Display Area 957.3 x 392.2 Display Area 957.3 x 392.2 Display Area 60.7 x 392.2 Olor Bit 0.182 Color Hit 0.182 Color Hit 3000K; 6500K; 9500K; User Define Gamma 1.8 -2.6 Display Mode 1.1 Aspect Ratio, Full HOCP 2.2 Uniformity Technology Ves Color Mode User]; User2; DCIPP3; Display P3, Rec.709; SRGB; HDR; M-book Built in Speaker 2.1 Channel (2Wx-2 + 5W woofer) Headphnon Jack Yes Till (down/up) 5"-20' Swiewel (left/right) 15'/15'		
Brightness (peak)(HDR) 400 Brightness (pys.) 350 HDR HDRTIO. VESA Display-HDR 400 Calor Gamut 100% aRGB: 100% Rec. 209; 95% P3 Factory Calibration Report Yes Celta (Equal) 2 Calman verified 4 % Native Contrast 1000-1 Refresh Rate (Hz) 60 Display Colors 1.07 billion colors Display Screen Coating Matte Iveal Pitch 6.03 Use Pitch 0.182 Color Bit 0.182 Color Temperature 5000K; 6500K; 9300K; User Define Gamma 1.8 - 2.6 Display Mode 1.1. Aspect Ratio. Full HDCP 2.2 Color Mode User1; User2; DCIP 30, Display P3, Rec. 709; SRGB; HDR; M-book Bull-In Speaker 2.1 channel (2w.2 + 9K woofer) Headhone Jack Yes Tiff (down/out) 5*-20° Silvan (left/right) 90° Height Adjustment Stand 1.15 mm VESA Valid Mount 100 x 10		
Brightness (typ.) 350		
HDR		
Color Gamut 100% RRGB; 100% Rec. 709; 95% P3 Factory Calibration Report Yes Delta E(avy) 42 Calman verified Yes Native Contrast 1000:1 Refresh Rate (Hz) 60 Display Osors 1.0 billion colors Display Area 697.3 x 392.2 Display Screen Coating Matte Pixel Pitch 0.182 Color Bit 10 Color Femperature 5000(x) 6500(x) 9300K. User Define Gamma 1.8 - 2.6 Display Mode 1:1; Aspect Ratio; Full HDCP 2.2 Unformity Technology Yes Color Mode User1; User2; DCLP3; Display P3; Rec. 709; sRGB; HDR; M-book Bullkin Speaker 2.1 Channel (ZWx.2 + SW woofer) Headphone Jack Yes Till (down/up) -5'-20' Swivel (left/right) 15'/15' Pvot 15'/15' Height Adjustment Stand 115mm VESA Wall Mount 100 x 100 LVSB Type-C X1 (PowerDeliver) 65W, DisplayPort Alt Mode, Da		
Pactor Calibration Report Peta		
Delta Eavay \$2 Calman verified Yes Native Contrast 1000:1 Refresh Rate (Hz) 60 Display Colors 1.07 billion colors Display Area 69.7 3 x 39.2 2 Display Screen Coating Matte Pixel Pitch 0.182 Color Bit 1.0 Color Temperature \$5000K; 5500K; 9300K; User Define Gamma 1.8 -2.6 Display Mode 1.1; Aspect Ratio, Full HOCP 2.2 Uniformity Technology Yes Color Mode User1; User2; DCI-P3: Display P9; Rec 709; sRGB; HDR; M-book Bullt-In Speaker 2.1 Channel (2Wx2 + 5W woofer) Headphone Jack Yes Till (down/Jup) 5'~20' Swivel (left/right) 15'715' Pivot 90' Height Adjustment Stand 115mm VESA Wall Mount 100 x 100 HDMI (9.2.0) X3 USB Type-C X1 (PowerDelivery 55W, DisplayPort Alt Mode, Data) USB Type-C downstream X1 (VSB 3.2 Gen 1, 5 Gbps, power ch		
Calman verified Yes Native Contrast 1000:1 Refresh Rate (Hz) 60 Display Colors 1.0 billion colors Display Area 697.3 x 39.2 z Display Screen Coating Matte Pixel Pixth 0.182 Color Bit 10 Color Temperature 5000K; 6500K; 9300K; User Define Gamma 1.8 - 2.6 Display Mode 1.1 x Aspect Ratio, Full HDCP Yes Color Mode User]; User2; DCI-P3; Display P3. Rec. 709; sRGB; HDR; M-book Bull-in Speaker 2.1 Channel (2Wx2 + 5W woofer) Headphone Jack Yes Till (down/up) 5-7-20' Swivel (left/right) 5-7-20' Swivel (left/right) 15/15' Pivot 90' Haight Adjustment Stand 115 mm VESA Wall Mount 100 x 100 HDMI (v2.0) X3 USB Type-C downstream x1 (PowerDelivery 65W, DisplayPort Alt Mode, Data) USB Type-C downstream x1 (WSB 3.2 Gen 1, 5 Gbps, power charging 7.5W) USB-C Typ		
Native Contrast 1000.1 Refresh Rate (Hz) 60 Display Colors 1.07 billion colors Display Area 697.3 x 392.2 Display Soreen Coating Mattee Pixel Pitch 0.182 Color Bit 10 Color Emperature 5000K; 6500K; 9300K; User Define Gamma 1.1; Aspect Ratio. Full HDCP 2.2 Uniformity Technology Ves Color Mode User1; User2; DCI-P3, Display P3; Rec. 709; RGB; HDR; M-book Sull-in Speaker 2.1 channel (2Wx2 + SW woofer) Headphone Jack Yes Till (down/ur) 5° -20° Swivel (left/right) 15'/15' Pvot 90° Height Adjustment Stand 115mm VESA Wall Mount 100 x 100 VESA Wall Mount 100 x 100 VESA Wall Mount 100 x 100 VESB Type-C x1 (PowerDelivery 65W, DisplayPort Alt Mode, Data) USB Type-C downstream x1 (USB 3.2 Gen 1, 5 Gbps, power charging 7.5W) USB Type-C downstream x1 (USB 3.2 Gen 1, 5 Gbps, power charging 7.		
Refresh Rate (Hz) 60 Display Colors 1.07 billion colors Display Area 697.3 x 392.2 Display Screen Coating Matte Privel Ptch 0.182 Color Bit 10 Color Temperature \$5000K; \$500K; \$900K; User Define Gamma 1.8 - 2.6 Display Mode 1.1.4 Spect Ratio; Full HDCP 2.2 Uniformity Technology Yes Color Mode User1; User2; DCI-P3; Display P3, Rec.709; sRGB; HDR; M-book Bull-in Speaker 2.1 Channel (2Wx2 + SW woofer) Headphone Jack Yes Tilt (down/up) 5.7 - 20' Swivel (left/right) 157/15' Pivot 90' Height Adjustment Stand 115mm VESA Wall Mount 100 x 100 HDMI (v2.0) x1 (PowerDelivery 65W, DisplayPort Alt Mode, Data) USB Type-C downstream x1 (USB 3.2 Gen.1, 5 Gbps, power charging 7.5 W) USB Type-C downstream x1 (USB 3.2 Gen.1, 5 Gbps, power charging 7.5 W) USB Type-C downstream x1 (USB 3.2 Gen.1, 5 Gbps, power charging 7.5 W)		
Display Colors 1.07 billion colors 1.0		
Display Area 697.3 x 392.2 Display Screen Coating Mattle Pixel Pitch 0.182 Color Bit 10 Color Temperature 5000K; 6500K; 9300K; User Define Gamma 1.8 - 2.6 Display Mode 1.1; Aspect Ratio; Full HDCP 2.2 Uniformity Technology Yes Color Mode User1; User2; DCI-P3; Display P3; Rec. 709; sRGB; HDR; M-book Bull-in Speaker 2.1 Channel (2Wx2 + 5W woofer) Headphone Jack Yes Tilt (down/up) 5'-20' Swivel (left/right) 15'/15' Pivot 90' Height Adjustment Stand 115mm VESA Wall Mount 100 x 100		
Display Screen Coating Matte Pixel Pitch 0.182 Color Bit 10 Color Temperature 5000K; 6500K; 9300K; User Define Gamma 1.8 - 2.6 Display Mode 1:1; Aspect Ratio; Full HDCP 2.2 Uniformity Technology Yes Color Mode User1; User2; DCI-P3; Display P3; Rec. 2709; RGB; HDR; M-book Bull-tin Speaker 2.1 Channel (2Wx2 + 5W woofer) Headphone Jack Yes Tilt (down/up) -5'-20' Swivel (left/right) 15'/15' Pivot 90' Height Adjustment Stand 115mm VESA Wall Mount 100 x 100 HDM (v2.0) x3 USB Type-C downstream x1 (PowerDeliver) 65W, DisplayPort Alt Mode, Data) USB Type-C downstream x3 (USB 3.2 cen 1, 5 Gbps, power charging 7.5W) USB Type-C downstream x3 (USB 3.2 cen 1, 5 Gbps, power charging 7.5W) Other Accessories Wireless Hotkey Puck (G3), QSG; Warranty Card; Calibration Report; Safety Instruction Power Cable 1.8 Signal Cable USB-C		
Pixel Pitch Color Bit 10		
Color Bit 10 Color Temperature \$5000K; \$5000K; \$9300K; User Define Gamma 1.8 - 2.6 Display Mode 1:1; Aspect Ratio; Full HDCP 2.2 Uniformity Technology Yes Color Mode User1; User2; DCI-P3; Display P3; Rec. 709; srGB; HDR; M-book Built in Speaker 2.1 Channel (2Wx2 + 5W woofer) Headphone Jack Yes Till (down/up) 5°-20° Swivel (left/right) 15'/15' Prot 90° Height Adjustment Stand 115 mm VESA Wall Mount 100 x 100 HDMI (v2.0) x3 USB Type-C downstream x1 (PowerDelivery 65W, DisplayPort Alt Mode, Data) USB Type-C downstream x1 (USB 3.2 Gen 1, 5 Gbps, power charging 7.5W) Other Accessories Wireless Hotkey Puck (G3); QSG; Warranty Card; Calibration Report; Safety Instruction Power Cable 1.8 Signal Cable 1.8 TUV Certificate Eye Comfort; EyeSafe 2.0; Flicker-free; Low Blue light (Hardware Solution) Low Blue Light Yes Flicker-free Technology	, ,	
Color Temperature 5000K; 6500K; 9500K; User Define Gamma 1.8 - 2.6 Display Mode 1:1; Aspect Ratio; Full HDCP 2.2 Uniformity Technology Yes Color Mode User1; User2; DCI-P3; Display P3; Rec.709; sRGB; HDR; M-book Built-in Speaker 2.1 Channel (2Wx2 + 5W woofer) Headphone Jack Yes Tilt (down/up) 5°-20° Swivel (left/right) 15'/15' Pivot 90° Height Adjustment Stand 115mm VESA Wall Mount 100 x 100 HDM (v2.0) x3 USB Type-C downstream x1 (PowerDelivery 65W, DisplayPort Alt Mode, Data) USB Type-C downstream x3 (USB 3.2 Gen 1, 5 Gbps, power charging 7.5W) USB Type-C downstream x3 (USB 3.2 Gen 1, 5 Gbps, power charging 7.5W) USB Type-C downstream x3 (USB 3.2 Gen 1, 5 Gbps, power charging 7.5W) USB Type-C downstream x3 (USB 3.2 Gen 1, 5 Gbps, power charging 7.5W) USB Type-C downstream x3 (USB 3.2 Gen 1, 5 Gbps, power charging 7.5W) USB Type-C downstream x3 (USB 3.2 Gen 1, 5 Gbps, power charging 7.5W) USB Type-		
Gamma 1.8: 2.6 Display Mode 1:1; Aspect Ratic; Full HDCP 2.2 Uniformity Technology Yes Color Mode User1; User2; DCI-P3; Display P3; Rec. 709; sRGB; HDR; M-book Built-in Speaker 2.1 Channel (2Wx2 + 5W woofer) Headphone Jack Yes Tillt (down/up) 5-20° Swivel (left/right) 15'715' Pivot 90° Height Adjustment Stand 115mm VESA Wall Mount 100 x 100 HDMI (v2.0) X3 USB Type-C X1 (Power Diever (56W, DisplayPort Alt Mode, Data) USB Type-C downstream X1 (ESB 3.2 Gen 1, 5 Gbps, power charging 7.5W) USB Type-A downstream X1 (USB 3.2 Gen 1, 5 Gbps, power charging 7.5W) USB Type-C downstream X1 (ESB 3.2 Gen 1, 5 Gbps, power charging 7.5W) USB Type-A downstream X1 (USB 3.2 Gen 1, 5 Gbps, power charging 7.5W) USB Type-A downstream X1 (USB 3.2 Gen 1, 5 Gbps, power charging 7.5W) USB Type-A downstream X1 (ESB 3.2 Gen 1, 5 Gbps, power charging 7.5W) USB Type-A downstream X1 (USB 3.2 Gen 1, 5 Gbps, power charging 7.5W)		
Display Mode HDCP 1:1; Aspect Ratio; Full Uniformity Technology 2.2 Color Mode User1; User2; DCI-P3; Display P3; Rec.709; sRGB; HDR; M-book Built-in Speaker 2.1 Channel (2Wx2 + 5W woofer) Headphone Jack Yes Tilt (down/up) 5-"20" Swivel (left/right) 90" Pivot 90" Height Adjustment Stand 115mm VESA Wall Mount 110mm USB Type-0 x3 USB Type-0 downstream x1 (PowerDelivery 65W, DisplayPort Alt Mode, Data) USB Type-0 downstream x1 (USB 3.2 Gen 1, 5 Gbps, power charging 7.5W) USB Type-0 downstream x3 (USB 3.2 Gen 1, 5 Gbps, power charging 7.5W) USB Type-0 downstream x3 (USB 3.2 Gen 1, 5 Gbps, power charging 7.5W) USB Type-0 downstream x3 (USB 3.2 Gen 1, 5 Gbps, power charging 7.5W) USB Type-0 downstream x3 (USB 3.2 Gen 1, 5 Gbps, power charging 7.5W) USB Type-0 downstream x3 (USB 3.2 Gen 1, 5 Gbps, power charging 7.5W) USB Type-0 downstream x3 (USB 3.2 Gen 1, 5 Gbps, power charging 7.5W) USB Type-0 downstream x3 (USB 3.2 Gen 1, 5 Gbps, power charging 7.5W) U		
HDCP		
Uniformity Technology Yes Color Mode User1; User2; DCI-P3; Display P3; Rec.709; RGB; HDR; M-book Built-in Speaker 2.1 Channel (2Wx2 + 5W woofer) Headphone Jack Yes Tilt (down/up) -5" ~20" Swivel (left/right) 15"/15" Pivot 90" Height Adjustment Stand 100 x 100 VESA Wall Mount 100 x 100 HDMI (v2.0) x3 USB Type-C downstream x1 (PowerDelivery 65W, DisplayPort Alt Mode, Data) USB Type-C downstream x1 (USB 3.2 Gen 1, 5 Gbps, power charging 7.5W) USB Type-C downstream x3 (USB 3.2 Gen 1, 5 Gbps, power charging 7.5W) USB Type-C downstream x3 (USB 3.2 Gen 1, 5 Gbps, power charging 7.5W) USB Type-C downstream x3 (USB 3.2 Gen 1, 5 Gbps, power charging 7.5W) USB Type-C downstream x3 (USB 3.2 Gen 1, 5 Gbps, power charging 7.5W) USB Type-C downstream x3 (USB 3.2 Gen 1, 5 Gbps, power charging 7.5W) USB Type-C downstream x3 (USB 3.2 Gen 1, 5 Gbps, power charging 7.5W) USB Type-C downstream Y6 (USB 3.2 Gen 1, 5 Gbps, power charging 7.5W) USB Type-C downstream X3 (USB 3.2 Gen 1, 5 Gbps, power charging 7		
Color Mode User1; User2; DCI-P3; Display P3; Rec. 709; sRGB; HDR; M-book Built-in Speaker 2.1 Channel (2Wx2 + 5W woofer) Headphone Jack Yes Tilt (down/up) -5*~20* Swivel (left/right) 15/15* Pivot 90° Height Adjustment Stand 115mm VESA Wall Mount 100 x 100 HDMI (v2.0) x3 USB Type-C downstream x1 (PowerDelivery 65W, DisplayPort Alt Mode, Data) USB Type-A downstream x3 (USB 3.2 Gen 1, 5 Gbps, power charging 7.5W) Other Accessories Wireless Hotkey Puck (G3); QSG; Warranty Card; Calibration Report; Safety Instruction Power Cable 1.8 Signal Cable USB-C TUV Certificate Eye Comfort; EyeSafe 2.0; Flicker-free; Low Blue light (Hardware Solution) Low Blue Light Yes Solidworks Yes Video Format Support Yes DualView Yes PIP/PBP Yes Auto Pivot No FW update by USB Yes ICCsync Yes Display ColorTalk		
Built-in Speaker 2.1 Channel (2Wx2 + 5W woofer) Headphone Jack Yes Tilt (down/up) 5°-20° Swivel (left/right) 15″/15″ Pivot 90° Height Adjustment Stand 115mm VESA Wall Mount 100 x 100 HDMI (v2.0) x3 USB Type-C downstream x1 (PowerDelivery 65W, DisplayPort Alt Mode, Data) USB Type-C downstream x1 (USB 3.2 Gen 1, 5 Gbps, power charging 7.5W) USB Type-C downstream x3 (USB 3.2 Gen 1, 5 Gbps, power charging 7.5W) USB Type-C downstream x3 (USB 3.2 Gen 1, 5 Gbps, power charging 7.5W) USB Type-C downstream x3 (USB 3.2 Gen 1, 5 Gbps, power charging 7.5W) USB Type-C downstream x3 (USB 3.2 Gen 1, 5 Gbps, power charging 7.5W) USB Type-C downstream x9 (USB 3.2 Gen 1, 5 Gbps, power charging 7.5W) USB Type-C downstream x9 (USB 3.2 Gen 1, 5 Gbps, power charging 7.5W) USB Type-C downstream x9 (USB 3.2 Gen 1, 5 Gbps, power charging 7.5W) USB Type-C downstream x9 (USB 3.2 Gen 1, 5 Gbps, power charging 7.5W) USB Type-C downstream x9 (USB 3.2 Gen 1, 5 Gbps, power charging 7.5W) USB Type-C downstream x9 (US	, 3,	
Headphone Jack Tilt (down/up) Swivel (left/right) Pivot Height Adjustment Stand VESA Wall Mount HDMI (v2.0) USB Type-C VS (Pye-C (Pye-C) VS (Py		
Tilt (down/up) -5°~20° Swivel (left/right) 15′/15° Pivot 90° Height Adjustment Stand 115mm VESA Wall Mount 100 x 100 HDMI (v2.0) x3 USB Type-C x1 (PowerDelivery 65W, DisplayPort Alt Mode, Data) USB Type-C downstream x1 (USB 3.2 Gen 1, 5 Gbps, power charging 7.5W) USB Type-A downstream x3 (USB 3.2 Gen 1, 5 Gbps, power charging 7.5W) USB Type-A downstream x3 (USB 3.2 Gen 1, 5 Gbps, power charging 7.5W) USB Type-A downstream x3 (USB 3.2 Gen 1, 5 Gbps, power charging 7.5W) USB Type-A downstream x3 (USB 3.2 Gen 1, 5 Gbps, power charging 7.5W) USB Type-A downstream x3 (USB 3.2 Gen 1, 5 Gbps, power charging 7.5W) USB Type-A downstream x3 (USB 3.2 Gen 1, 5 Gbps, power charging 7.5W) USB Type-A downstream x9 (USB 3.2 Gen 1, 5 Gbps, power charging 7.5W) USB Type-C downstream x9 (USB 3.2 Gen 1, 5 Gbps, power charging 7.5W) USB Type-C downstream x9 (USB 3.2 Gen 1, 5 Gbps, power charging 7.5W) USB Type-C downstream x9 (USB 3.2 Gen 1, 5 Gbps, power charging 7.5W) USB Type-C downstream x9 (USB 3.2 Gen 1, 5 Gbps, power charging 7.5W)		
Swivel (left/right) 15'/15' Pivot 90' Height Adjustment Stand 115mm VESA Wall Mount 100 x 100 HDMI (v2.0) x3 USB Type-C downstream x1 (PowerDelivery 65W, DisplayPort Alt Mode, Data) USB Type-A downstream x1 (USB 3.2 Gen 1, 5 Gbps, power charging 7.5W) USB Type-A downstream x3 (USB 3.2 Gen 1, 5 Gbps, power charging 7.5W) Other Accessories Wireless Hotkey Puck (G3); QSG; Warranty Card; Calibration Report; Safety Instruction Power Cable 1.8 Signal Cable USB-C TUV Certificate Eye Comfort; EyeSafe 2.0; Flicker-free, Low Blue light (Hardware Solution) Low Blue Light Yes Flicker-free Technology Yes Solidworks Yes Video Format Support Yes DualView Yes PIP/PBP Yes Auto Pivot No FW update by USB Yes ICCsync Yes Display Pilot 2 Yes Palette Master Ultimate Yes Display ColorTalk Yes		
Pivot Height Adjustment Stand 115mm VESA Wall Mount 100 x 100 HDMI (v2.0) x3 USB Type-C X1 (PowerDelivery 65W, DisplayPort Alt Mode, Data) USB Type-C downstream x3 (USB 3.2 Gen 1, 5 Gbps, power charging 7.5W) Other Accessories X1 (USB 3.2 Gen 1, 5 Gbps, power charging 7.5W) Other Accessories Wireless Hotkey Puck (G3); QSG; Warranty Card; Calibration Report; Safety Instruction Power Cable USB-C TUV Certificate Eye Comfort; EyeSafe 2.0; Flicker-free; Low Blue light (Hardware Solution) Low Blue Light Yes Flicker-free Technology Yes Solidworks Yes Video Format Support Yes DualView Pip/PBP Yes Auto Pivot No FW update by USB ICCSync Display Pilot 2 Palette Master Ultimate Display ColorTalk Power Cable 100 x 1		
Height Adjustment Stand VESA Wall Mount HDMI (v2.0) USB Type-C USB Type-C downstream USB Type-A downstream X3 (USB 3.2 Gen 1, 5 Gbps, power charging 7.5W) Wireless Hotkey Puck (G3); QSG; Warranty Card; Carlibration Report; Safety Instruction Power Cable USB-C TUV Certificate USB-C TUV Certificate Eye Comfort; EyeSafe 2.0; Flicker-free; Low Blue light (Hardware Solution) Ves Flicker-free Technology Yes Video Format Support Ves Video Format Support Ves Video Format Support Ves PIP/PBP Auto Pivot FW update by USB ICCSync Display Pilot 2 Palette Master Ultimate Display ColorTalk Yes		
VESA Wall Mount 100 x 100 HDMI (v2.0) x3 USB Type-C x1 (PowerDelivery 65W, DisplayPort Alt Mode, Data) USB Type-C downstream x1 (USB 3.2 Gen 1, 5 Gbps, power charging 7.5W) USB Type-A downstream x3 (USB 3.2 Gen 1, 5 Gbps, power charging 7.5W) Other Accessories Wireless Hotkey Puck (G3); QSG; Warranty Card; Calibration Report; Safety Instruction Power Cable 1.8 Signal Cable USB-C TUV Certificate Eye Comfort; EyeSafe 2.0; Flicker-free; Low Blue light (Hardware Solution) Low Blue Light Yes Flicker-free Technology Yes Solidworks Yes Video Format Support Yes Dual View Yes PIP/PBP Yes Auto Pivot No FW update by USB Yes ICCsync Yes Display Pilot 2 Yes Palette Master Ultimate Yes Display ColorTalk Yes		
HDMI (v2.0) USB Type-C USB Type-C (
USB Type-C with the comment of the c		
USB Type-C downstream USB Type-A downstream USB Type-A downstream X1 (USB 3.2 Gen 1, 5 Gbps, power charging 7.5W) USB Type-A downstream X3 (USB 3.2 Gen 1, 5 Gbps, power charging 7.5W) USB Type-A downstream X3 (USB 3.2 Gen 1, 5 Gbps, power charging 7.5W) USB Type-A downstream X3 (USB 3.2 Gen 1, 5 Gbps, power charging 7.5W) USB Type-A downstream X3 (USB 3.2 Gen 1, 5 Gbps, power charging 7.5W) USB Type-A downstream X3 (USB 3.2 Gen 1, 5 Gbps, power charging 7.5W) X4 (USB 3.2 Gen 1, 5 Gbps, power charging 7.5W) X5 (USB 3.2 Gen 1, 5 Gbps, power charging 7.5W) X5 (USB 3.2 Gen 1, 5 Gbps, power charging 7.5W) X5 (USB 3.2 Gen 1, 5 Gbps, power charging 7.5W) X5 (USB 3.2 Gen 1, 5 Gbps, power charging 7.5W) X5 (USB 3.2 Gen 1, 5 Gbps, power cherging 7.5W) X5 (USB 3.2 Gen 1, 5 Gbps, power cherging 7.5W) X5 (USB 3.2 Gen 1, 5 Gbps, power charging 7.5W) X5 (USB 3.2 Gen 1, 2 Geps, power charging 7.5W) X5 (USB 3.2 Gen 1, 2 Geps, power cherging 7.5W) X5 (USB 3.2 Gen 1, 2 Geps, power cherging 7.5W		
USB Type-A downstream Other Accessories Other Accessories Power Cable Signal Cable USB-C TUV Certificate Low Blue Light Flicker-free Technology Solidworks Video Format Support DualView PIP/PBP Auto Pivot FW update by USB ICCSync Display Pilot 2 Palette Master Ultimate Display ColorTalk X3 (USB 3.2 Gen 1, 5 Gbps, power charging 7.5W) Wireless Hotkey Puck (G3); QSG; Warranty Card; Calibration Report; Safety Instruction PW Wireless Hotkey Puck (G3); QSG; Warranty Card; Calibration Report; Safety Instruction USB-C USB-C Eye Comfort; EyeSafe 2.0; Flicker-free; Low Blue light (Hardware Solution) Fyes Eye Comfort; EyeSafe 2.0; Flicker-free; Low Blue light (Hardware Solution) Fyes Eye Comfort; EyeSafe 2.0; Flicker-free; Low Blue light (Hardware Solution) Fyes Eye Comfort; EyeSafe 2.0; Flicker-free; Low Blue light (Hardware Solution) Fyes Eye Comfort; EyeSafe 2.0; Flicker-free; Low Blue light (Hardware Solution) Fyes Eye Comfort; EyeSafe 2.0; Flicker-free; Low Blue light (Hardware Solution) Fyes Eye Comfort; EyeSafe 2.0; Flicker-free; Low Blue light (Hardware Solution) Fyes Eye Comfort; EyeSafe 2.0; Flicker-free; Low Blue light (Hardware Solution) Fyes Eye Comfort; EyeSafe 2.0; Flicker-free; Low Blue light (Hardware Solution) Fyes Eye Comfort; EyeSafe 2.0; Flicker-free; Low Blue light (Hardware Solution) Fyes Eye Comfort; EyeSafe 2.0; Flicker-free; Low Blue light (Hardware Solution) Fyes Eye Comfort; EyeSafe 2.0; Flicker-free; Low Blue light (Hardware Solution) Fyes Eye Comfort; EyeSafe 2.0; Flicker-free; Low Blue light (Hardware Solution) Fyes Eye Comfort; EyeSafe 2.0; Flicker-free; Low Blue light (Hardware Solution) Fyes Eye Comfort; EyeSafe 2.0; Flicker-free; Low Blue light (Hardware Solution) Fyes Eye Comfort; EyeSafe 2.0; Flicker-free; Low Blue light (Hardware Solution) Fyes Eye Comfort; EyeSafe 2.0; Flicker-free; Low Blue light (Hardware Solution) Fyes Eye Comfort; EyeSafe 2.0; Flicker-free; Low Blue light (Hardware Solution) Fyes Eye Comfort; EyeSafe 2.0; Flicker-free; Low Blue light (Hardware		
Other AccessoriesWireless Hotkey Puck (G3); QSG; Warranty Card; Calibration Report; Safety InstructionPower Cable1.8Signal CableUSB-CTUV CertificateEye Comfort; EyeSafe 2.0; Flicker-free; Low Blue light (Hardware Solution)Low Blue LightYesFlicker-free TechnologyYesSolidworksYesVideo Format SupportYesDualViewYesPIP/PBPYesAuto PivotNoFW update by USBYesICCsyncYesDisplay Pilot 2YesPalette Master UltimateYesDisplay ColorTalkYes		
Power Cable1.8Signal CableUSB-CTUV CertificateEye Comfort; EyeSafe 2.0; Flicker-free; Low Blue light (Hardware Solution)Low Blue LightYesFlicker-free TechnologyYesSolidworksYesVideo Format SupportYesDualViewYesPIP/PBPYesAuto PivotNoFW update by USBYesICCsyncYesDisplay Pilot 2YesPalette Master UltimateYesDisplay ColorTalkYes		
Signal CableUSB-CTUV CertificateEye Comfort; EyeSafe 2.0; Flicker-free; Low Blue light (Hardware Solution)Low Blue LightYesFlicker-free TechnologyYesSolidworksYesVideo Format SupportYesDualViewYesPIP/PBPYesAuto PivotNoFW update by USBYesICCsyncYesDisplay Pilot 2YesPalette Master UltimateYesDisplay ColorTalkYes		
TUV Certificate Eye Comfort; EyeSafe 2.0; Flicker-free; Low Blue light (Hardware Solution) Low Blue Light Yes Flicker-free Technology Yes Solidworks Yes Video Format Support Yes DualView Yes PIP/PBP Yes Auto Pivot No FW update by USB ICCsync Yes Display Pilot 2 Yes Display ColorTalk Eye Comfort; EyeSafe 2.0; Flicker-free; Low Blue light (Hardware Solution) Yes Yes No Yes Yes Yes Yes Yes Yes Palette Master Ultimate Display ColorTalk Yes		
Low Blue Light Yes Flicker-free Technology Yes Solidworks Yes Video Format Support Yes DualView Yes PIP/PBP Yes Auto Pivot No FW update by USB ICCsync Yes Display Pilot 2 Yes Palette Master Ultimate Yes Display ColorTalk Yes	· ·	
Flicker-free Technology Solidworks Video Format Support DualView PIP/PBP Auto Pivot FW update by USB ICCsync Display Pilot 2 Palette Master Ultimate Display ColorTalk Yes Yes Yes Yes Yes Yes Yes Ye		
Solidworks Yes Video Format Support Yes DualView Yes PIP/PBP Yes Auto Pivot No FW update by USB Yes ICCsync Yes Display Pilot 2 Yes Palette Master Ultimate Yes Display ColorTalk Yes	ÿ	
Video Format Support Yes DualView Yes PIP/PBP Yes Auto Pivot No FW update by USB Yes ICCsync Yes Display Pilot 2 Yes Palette Master Ultimate Yes Display ColorTalk Yes	9,	
DualViewYesPIP/PBPYesAuto PivotNoFW update by USBYesICCsyncYesDisplay Pilot 2YesPalette Master UltimateYesDisplay ColorTalkYes		
PIP/PBP Yes Auto Pivot No FW update by USB Yes ICCsync Yes Display Pilot 2 Yes Palette Master Ultimate Yes Display ColorTalk Yes		
Auto PivotNoFW update by USBYesICCsyncYesDisplay Pilot 2YesPalette Master UltimateYesDisplay ColorTalkYes		
FW update by USB Yes ICCsync Yes Display Pilot 2 Yes Palette Master Ultimate Yes Display ColorTalk Yes		
ICCsyncYesDisplay Pilot 2YesPalette Master UltimateYesDisplay ColorTalkYes		
Display Pilot 2 Yes Palette Master Ultimate Yes Display ColorTalk Yes		
Paletté Master Ultimate Yes Display ColorTalk Yes		
Display ColorTalk Yes		
	Display ColorTalk	
	Display Quickit	Yes
Dimensions (HxWxD) (mm) 480.22 ~ 595.22 x 714.5 x 210.46	Dimensions (HxWxD) (mm)	
Dimensions (HxWxD) (inch) 18.91 x 28.13 x 8.29	Dimensions (HxWxD) (inch)	
Net Weight (kg / lb) 8.73 kg / 18.67 lbs	Net Weight (kg / lb)	
Gross Weight (kg / lb) 12.62 kg / 27.82 lbs	Gross Weight (kg / lb)	12.62 kg / 27.82 lbs
Voltage Rating 100 - 240V		100 - 240V
Power Consumption (normal/max/sleep mode) 50 / 180 / 0.5		50 / 180 / 0.5
		Greek; Bulgarian; Ukrainian; Arabic; Chinese (simplified); Chinese (traditional); Czech; Deutsch; English;

Greek; Bulgarian; Ukrainian; Arabic; Chinese (simplified); Chinese (traditional); Czech; Deutsch; English; French; Hungarian; Italian; Japanese; Korean; Netherlands; Polish; Portuguese; Romanian; Russian; Spanish; Swedish



